


WCP1A

Conventional Weatherproof Manual Call Point

Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor
- ▶ Other colours available on request
- ▶ Ingress Protection rated to IP67
- ▶ Approved by LPCB.



Description

The WCP1A is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals.

The unit can support either a 'Frangible Glass' element or a 'Non Frangible Plastic' element and features a weatherproof Housing to IP67, which means

it can be mounted in the most severe environmental conditions without water ingress.

IMPORTANT NOTE: After changing the element from Glass to Flexi, please confirm the operation by pressing the resettable element.

Specification

Ordering codes	WCP1A - Red			
Nominal operating resistance	470 Ω			
Maximum contact resistance	200 Ω			
IP rating	IP67			
Operating / Storage temperature range	- 25 °C to + 70 °C			
Maximum humidity	95% RH - Non-condensing (at 40 °C)			
Colour / Case material	Red / ABS			
Weight (g) / Dimensions (mm)	234 / W 98 x H 94 x D 78			
Accessories	Frangible element	KAC / G / HE	Non-frangible element	KAC / EWS / HE



For further information visit our website. Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.

