

DCD-CE3M

Marine Approved Conventional Combined Rate of Rise & Fixed Temperature Heat Detector (90°C)

Features

- ▶ Electronic linear heat detection
- ▶ Incorporates a 90° C fixed temperature element
- ▶ Remote Indicator output
- ▶ Wide voltage range (9.5 ~ 30 V dc)
- ▶ Twin fire LEDs allow 360° viewing
- ▶ Approved for marine use by DNV.



Description

Model DCD-CE3M is a Rate of Rise Heat Detector with a 90 °C fixed temperature element using a thermistor and linearising circuit to provide an accurate linear response Heat Detector.

The DCD-CE3M is ideal for use where medium ambient temperatures exist, such as drying rooms or where Smoke Detectors are unsuitable because of the presence of steam or cooking fumes such as in a kitchen.

The DCD-CE3M is supported by a wide range of bases for different applications and these are supported on the majority of conventional systems. A third terminal provides remote indicator output.

Specification

Ordering code	DCD-CE3M
Operating voltage	9.5 – 30 VDC
Quiescent current	35 µA
Maximum current in alarm (typical)	40 mA
Remote indicator drive	20 mA (max) / 9.5-14 mA (typ)
IP rating	IP63
Maximum humidity	95% RH - Non condensing (at 40°C)
Operating Temperature Range	-10 °C to +50 °C
Storage Temperature Range	-30 °C to +70 °C
Colour / Case material	Ivory / Polycarbonate
Compatible bases	YBN-R/6M
Base fixing centres (mm)	48 ~ 74
Weight (g) / Dimensions (mm)	76 / Ø 100 x H 38
Approvals to (EN54:2000) Class A1 & A1R	DNV



For further information visit our website. Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.

